

SPECIFICATIONS

Dimensions (inches)



Condenser



Evaporator

Description

The TriPac Evolution provides truck engine preheating, battery charging, truck cab sleeper compartment climate control and electric power.

Engine

Thermo King Tier IV final-compliant 2-cylinder diesel engine

Evaporator Airflow

250 ft³/min

Alternator

14.5V, 65 amp
14.5V, 120 amp (optional)

Refrigerant

HFC R-134a

Compressor

Thermo King TM-15
Air Conditioning Compressor

Air Conditioning Capacity*

BTU/hr	Watts
13,000	3,810

Controls

The TriPac HMI (Human Machine Interface) Controller features a simple three-knob design for easy operation.

Heating Capacity

BTU/hr	Watts
7,500	2,200
13,600	3,986 (optional)

System Weight (approx.)

APU Unit:	345 lbs	(156 kg)
HVAC System:	70 lbs	(32 kg)

Warranty Summary

Terms of the Thermo King Limited Express Warranty are available upon request.

Extended Warranty

Several Extended Warranty options are available for your TriPac system. Choose a flexible program and select the warranty period, deductible and hours of operation that best meet your needs. Ask your local Thermo King dealer about nationwide coverage plans.

***ARI STD 310/380** - Standard for Packaged Terminal Air-Conditioners and Heat Pumps for the rating conditions of 80F Box, 50% humidity, and 95°F ambient.



New Thermo Gard™ Assurance

CUSTOMIZABLE FLEET MANAGEMENT OPTIONS FOR YOUR BUSINESS ARE NOW MORE AFFORDABLE THAN EVER BEFORE*

Thermo King SVC's new Thermo Gard Assurance guaranteed maintenance program includes set programs and a wide variety of coverage options to fit the needs of your business. And because of the TriPac Evolution's improved reliability and lower maintenance costs, peace-of-mind is now less expensive than ever!

*Compared to similar guaranteed maintenance program costs for TriPac APUs.